



MG-YDE-0029/M

YANGDONG Series Diesel Generator Sets

Stand by	COS PHI	0,8	1
	kVA	28,8	
	kW	23	

PRIME	COS PHI	0,8	1
	kVA	26,1	
	kW	20,9	



YANGDONG



EMSA



Smart 500 mk



Water Cooled



50 hz



1 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



Engine Specifications

- YANGDONG series heavy duty diesel engine
- 4 Cycle, Water Cooling system, Natural Induction
- Mechanic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	YSD490D	
Power	Stand by kW	27
	Prime kW	24,5
Speed (rpm)	1500	
Cycle	4	
Displacement (lt)	2,54	
Number of cylinders	4, in line	
Bore & Stroke	90 x 100	
Compression ratio	18 : 1	

Governor type	Mechanic	
Induction	Natural	
Combustion System	Direct	
Cooling system	Water	
Fuel consumption 100% (lt/h)	5,45	
	75%	
	4,05	
50%	2,98	
Total lubrication system capacity (lt)	8	
Total coolant capacity (lt)	14	



Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid

Brand	EMSA	
Model	EGK180-36N2	
Frequency (hz)	50	
Power (KVA) (Phi 0,8/1)	29/23	
Design	4 pole, brushless	
Connection type	Double Delta	
Voltage (V)	220	

phase	1	
A.V.R.	SX460	
Voltage regulation (+/-)	± 1%	
Insulation system	Class H	
Protection	IP23	
Rated power factor		
Weight (kg)	222	



Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



Dimensions
(W x L x H) mm

900x1900x1220



Weight (Kg)

728,6



Fuel tank capacity (lt)

101

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system



Dimensions
(W x L x H) mm

900 x 1600 x 1220



Weight (Kg)

574,6



Fuel tank capacity (lt)

101

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

Canopy options

- Standard canopy
- Super silent canopy
- Extra süper silent canopy (thicker insulation)

Optional Equipments

- Charge ammeter
- Moulded case circuit braker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water seperator filter
- PMG warning system