



MG-BDE-0660

BAUDOUIN Series Diesel Generator Sets

Stand by	kVA	660
	kW	528

PRIME	kVA	600
	kW	480



BAUDOUIN



EMSA



Smart 500 mk



Water Cooled



50 hz



3 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



Engine Specifications

- BAUDOUIN series heavy duty diesel engine
- 4 Cycle, Water Cooling system, TURBOCHARGED - AFTERCOOLER Induction
- PDF_BLOK4_ENGINE_SPECIFICATIONS_GOVERNOR_ECU governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	8M21G660/5	
Power	Stand by kW	580
	Prime kW	530
Speed (rpm)	1500	
Cycle	4	
Displacement (lt)	19,6	
Number of cylinders	8 V	
Bore & Stroke	127 x 165	
Compression ratio	15 : 1	

Governor type	PDF_BLOK4_ENGINE_SPECIFICATIONS_GOVERNOR_ECU	
Induction	TURBOCHARGED - AFTERCOOLER	
Combustion System	Direct	
Cooling system	Water	
Fuel consumption 100%	124,2	
(lt/h)	75%	95,4
	50%	64,7
Total lubrication system capacity (lt)	45	
Total coolant capacity (lt)	101	



Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid



Brand	EMSA
Model	EGK355-470N
Frequency (hz)	50
Power (KVA)	660
Design	4 pole, brushless
Connection type	Star
Voltage (V)	400

phase	3
A.V.R.	KR440
Voltage regulation (+/-)	± 1%
Insulation system	Class H
Protection	IP23
Rated power factor	0,8
Weight (kg)	1543



Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



Dimensions
(W x L x H) mm

1618x4200x2810 *



Weight (Kg)

5530,4



Fuel tank capacity (lt)

885

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system



Dimensions
(W x L x H) mm

1600x3500x1950



Weight (Kg)

4742



Fuel tank capacity (lt)

885

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

Canopy options

- Standard canopy
- Super silent canopy
- Extra süper silent canopy (thicker insulation)

Optional Equipments

- Charge ammeter
- Moulded case circuit braker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water seperator filter
- PMG warning system