



MG-BDS-2550

BAUDOUIN Series Diesel Generator Sets

Stand by	kVA	2550
	kW	2040

PRIME	kVA	2304
	kW	1843



BAUDOUIN



STAMFORD



Smart 500 mk



Water Cooled



50 hz



3 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



Engine Specifications

- BAUDOUIN series heavy duty diesel engine
- 4 Cycle, Water Cooling system, TURBOCHARGED - AFTERCOOLER Induction
- PDF_BLOK4_ENGINE_SPECIFICATIONS_GOVERNOR_ECU governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	12M55G2550/5	
Power	Stand by kW	2210
	Prime kW	1985
Speed (rpm)	1500	
Cycle	4	
Displacement (lt)	65,65	
Number of cylinders	12 V	
Bore & Stroke	180 x 215	
Compression ratio	16.5 : 1	

Governor type	PDF_BLOK4_ENGINE_SPECIFICATIONS_GOVERNOR_ECU	
Induction	TURBOCHARGED - AFTERCOOLER	
Combustion System	Direct	
Cooling system	Water	
Fuel consumption 100%	464	
(lt/h)	75%	366,2
	50%	231,6
Total lubrication system capacity (lt)	560	
Total coolant capacity (lt)	N/A	



Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid

Brand	STAMFORD
Model	PI734H
Frequency (hz)	50
Power (KVA)	2600
Design	4 pole, brushless
Connection type	Star
Voltage (V)	400

phase	3
A.V.R.	DECS100
Voltage regulation (+/-)	± 0,5%
Insulation system	Class H
Protection	IP23
Rated power factor	0,8
Weight (kg)	-




Container

- Chassis parts and load-bearing construction are manufactured from 140mm NPU
- The base metal sheet is manufactured from 2/3 diamond-shaped metal sheet
- Sidewall metal sheets are manufactured from 1.5mm ST 37 DKP trapezoidal metal sheet
- The top metal sheet will be manufactured from 1.5mm ST 37 DKP trapezoidal metal sheet
- Air disposing and suction parts are manufactured with the normal shutter in bolt-mounted hot-plug
- Lifting lugs are manufactured to bear the total load of the container (with generator)(8 pcs ISO Locked)
- PPG RAL 9010 paint application is followed for painting
- Internal illumination has 2x1x18 Watt waterproof fixture and 1x1x16 A monophasic plug fitting

- Top wall isolation is 0.8mm galvanised perforated metal sheet coating on 8cm fibro-glass glass wool plate
- The double-winged main door is manufactured with a pipe-type locking mechanism
- Service doors are manufactured with 4 single-winged and internal panic bar mechanisms to be locked outside (These doors are designed mounted inside the container body and doorknobs do not exceed container body)
- Emergency stop button on long edges
- Warning signs are placed to necessary places inside and outside the container




 Dimensions (W x L x H) mm -X-X-

 Weight (Kg) 0

 Fuel tank capacity (lt) -



 Dimensions (W x L x H) mm -X-X-

 Weight (Kg) 0

 Fuel tank capacity (lt) -

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Container Options

- Standard container
- Acoustic container

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

- Over current load
- High & low genset voltage
- Start/stop failure

Optional Equipments

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system