



## MG-PRE-0088

PERKINS Series Diesel Generator Sets

Stand by	kVA	88
	kW	70

PRIME	kVA	80
	kW	64



PERKINS



EMSA



Smart 500 mk



Water Cooled



50 hz



3 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



## Engine Specifications

- PERKINS series heavy duty diesel engine
- 4 Cycle, Water Cooling system, TURBOCHARGED - INTERCOOLER Induction
- Mechanic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	1104A-44TG2	
Power	Stand by kW	79,1
	Prime kW	71,9
Speed (rpm)	1500	
Cycle	4	
Displacement (lt)	4,4	
Number of cylinders	4, in line	
Bore & Stroke	105 x 127	
Compression ratio	17,25 : 1	

Governor type	Mechanic	
Induction	TURBOCHARGED - INTERCOOLER	
Combustion System	Direct	
Cooling system	Water	
Fuel consumption (lt/h)	100%	18,7
	75%	14
	50%	9,7
Total lubrication system capacity (lt)	8	
Total coolant capacity (lt)	13	



## Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid


Brand	EMSA	
Model	EGK225-70N	
Frequency (hz)	50	
Power (KVA)	92	
Design	4 pole, brushless	
Connection type	Star	
Voltage (V)	400	

phase	3	
A.V.R.	SX460	
Voltage regulation (+/-)	± 1%	
Insulation system	Class H	
Protection	IP23	
Rated power factor	0,8	
Weight (kg)	383	



## Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



Dimensions (W x L x H) mm 1000x2600x1535



Weight (Kg) 1309,4



Fuel tank capacity (lt) 139

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system



Dimensions (W x L x H) mm 1000x2200x1385



Weight (Kg) 1073



Fuel tank capacity (lt) 139

### Silencer options

- Standard industrial type
- Critical type
- Hospital type

### Canopy options

- Standard canopy
- Super silent canopy
- Extra süper silent canoy (thicker insulation)

### Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

- Over current load
- High & low genset voltage
- Start/stop failure

### Optional Equipments

- Charge ammeter
- Moulded case circuit braker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water seperator filter
- PMG warning system