



MG-PRS-0010

PERKINS Series Diesel Generator Sets

Stand by	kVA	10
	kW	8

PRIME	kVA	9
	kW	7



PERKINS



STAMFORD



Smart 500 mk



Water Cooled



50 Hz



3 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



Engine Specifications

- PERKINS series heavy duty diesel engine
- 4 Cycle, Water Cooling system, Natural Induction
- Mechanic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	403A-11G1		Governor type	Mechanic
Power	Stand by kW	9,2	Induction	Natural
	Prime kW	8,4	Combustion System	Indirect
Speed (rpm)	1500		Cooling system	Water
Cycle	4		Fuel consumption 100%	3
Displacement (lt)	1,131		(lt/h) 75%	2,3
Number of cylinders	3, in line		50%	1,7
Bore & Stroke	77 x 81		Total lubrication system capacity (lt)4,9	
Compression ratio	23 : 1		Total coolant capacity (lt) 5,2	



Alternator Specifications



- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid

Brand	STAMFORD	phase	3
Model	SOL1-H1	A.V.R.	DM710
Frequency (hz)	50	Voltage regulation (+/-)	± 1%
Power (KVA)	11	Insulation system	Class H
Design	4 pole, brushless	Protection	IP23
Connection type	Star	Rated power factor	0,8
Voltage (V)	400	Weight (kg)	60



Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



Dimensions
(W x L x H) mm

900x1750x1337



Weight (Kg)

470,4



Fuel tank capacity (lt)

82

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system



Dimensions
(W x L x H) mm

900x1400x1145



Weight (Kg)

294



Fuel tank capacity (lt)

82

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

Canopy options

- Standard canopy
- Super silent canopy
- Extra süper silent canopy (thicker insulation)

Optional Equipments

- Charge ammeter
- Moulded case circuit braker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water seperator filter
- PMG warning system