





MG-SDS-0165

SDEC Series Diesel Generator Sets

Stand by	kVA	165
	kW	132

PRIME	kVA	150
	kW	120



Engine Specifications

- SDEC series heavy duty diesel engine
- 4 Cycle, Water Cooling system, TURBOCHARGED - INTERCOOLER Induction
- Electronic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	SC4H180D2		Governor type	Electronic
Power	Stand by kW	132	Induction	TURBOCHARGED - INTERCOOLER
	Prime kW	126		
Speed (rpm)	1500		Combustion System	Direct
Cycle	4		Cooling system	Water
Displacement (lt)	4,3		Fuel consumption (lt/h)	100%
Number of cylinders	4, in line			75%
Bore & Stroke	105 x 124			50%
Compression ratio	16 : 1		Total lubrication system capacity (lt)	13
			Total coolant capacity (lt)	21

Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid

Brand	STAMFORD	phase	3
Model	UCI274F	A.V.R.	SX460
Frequency (hz)	50	Voltage regulation (+/-)	± 0,5%
Power (KVA)	175	Insulation system	Class H
Design	4 pole, brushless	Protection	IP23
Connection type	Star	Rated power factor	0,8
Voltage (V)	400	Weight (kg)	530



Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



Dimensions (W x L x H) mm 1100x3100x1845



Weight (Kg) 1530,6



Fuel tank capacity (lt) 275

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system



Dimensions (W x L x H) mm 1100x2600x1640



Weight (Kg) 1227



Fuel tank capacity (lt) 275

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Canopy options

- Standard canopy
- Super silent canopy
- Extra süper silent canoy (thicker insulation)

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

- Over current load
- High & low genset voltage
- Start/stop failure

Optional Equipments

- Charge ammeter
- Moulded case circuit braker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water seperator filter
- PMG warning system