



MG-BDS-0032/6

BAUDOUIN Series Diesel Generator Sets

Stand by	kVA	32
	kW	26

PRIME	kVA	29
	kW	23



BAUDOUIN



STAMFORD



Smart 500 mk



Water Cooled



60 hz



3 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



Engine Specifications

- BAUDOUIN series heavy duty diesel engine
- 4 Cycle, Water Cooling system, Natural Induction
- Electronic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	4M06G25/6		Governor type	Electronic	
Power	Stand by kW	30	Induction	Natural	
	Prime kW	27	Combustion System	Direct	
Speed (rpm)	1800		Cooling system	Water	
Cycle	4		Fuel consumption 100%	7,3	
Displacement (lt)	2,3		(lt/h)	75%	5,3
Number of cylinders	4, in line			50%	3,8
Bore & Stroke	89 x 92		Total lubrication system capacity (lt) 11,5		
Compression ratio	17,5 : 1		Total coolant capacity (lt) 16		



Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid



Brand	STAMFORD		Voltage regulation (+/-)	± 1%	
Frequency (hz)	60		Insulation system	Class H	
Design	4 pole, brushless		Protection	IP23	
phase	3		Rated power factor	0,8	

Brand	Voltage (V)	Stand by	Continuous	A.V.R.	Connection type	Weight (kg)
S0L2-P	220	36,9	33,6	AS540	Parallel Star	132
S0L2-P	380	31,4	28,5	AS540	Series Star	132
S0L2-P	440	36,9	33,6	AS540	Series Star	132



Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



Dimensions
(W x L x H) mm

900x1700x1220



Weight (Kg)

650



Fuel tank capacity (lt)

82

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system



Dimensions
(W x L x H) mm

900x1400x1220



Weight (Kg)

504



Fuel tank capacity (lt)

82

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

Optional Equipments

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

Canopy options

- Standard canopy
- Super silent canopy
- Extra super silent canopy (thicker insulation)

- Over current load
- High & low genset voltage
- Start/stop failure

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system