



MG-IVS-0294/6

FPT - IVECO Series Diesel Generator Sets

Stand by	kVA	294
	kW	235,2

PRIME	kVA	267
	kW	213,6



FPT - IVECO



STAMFORD



Smart 500 mk



Water Cooled



60 hz



3 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



Engine Specifications

- FPT - IVECO series heavy duty diesel engine
- 4 Cycle, Water Cooling system, TURBOCHARGED - AFTERCOOLER Induction
- Electronic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	NEF67TE8W.S550		Governor type	Electronic
Power	Stand by kW	255	Induction	TURBOCHARGED - AFTERCOOLER
	Prime kW	231		
Speed (rpm)	1800		Combustion System	Direct
Cycle	4		Cooling system	Water
Displacement (lt)	6,7		Fuel consumption 100% (lt/h)	56,3
Number of cylinders	6, in line			75%
Bore & Stroke	104X132		50%	28,7
Compression ratio	17 : 1		Total lubrication system capacity (lt)	17,2
			Total coolant capacity (lt)	30,5



Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid

Brand	STAMFORD		Voltage regulation (+/-)	± 1%
Frequency (hz)	60		Insulation system	Class H
Design	4 pole, brushless		Protection	IP23
phase	3		Rated power factor	0,8

Brand	Voltage (V)	Stand by	Continuous	A.V.R.	Connection type	Weight (kg)
UCDI274K	220	320	299	SX460	Parallel Star	727
S4L1D-D	380	354,1	319,6	AS440	Series Star	940
UCDI274K	440	320	299	SX460	Series Star	727



Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



Dimensions (W x L x H) mm 1200 x 3600 x 2490



Weight (Kg) 2460,7



Fuel tank capacity (lt) 360

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system



Dimensions (W x L x H) mm 1200x3100x2490



Weight (Kg) 2142,7



Fuel tank capacity (lt) 360

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Canopy options

- Standard canopy
- Super silent canopy
- Extra süper silent canopy (thicker insulation)

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

- Over current load
- High & low genset voltage
- Start/stop failure

Optional Equipments

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system