

MGT- BDE-1100

BAUDOUIN Series Twin Diesel Generator Sets

Stand by	kVA	1100
	kW	880

PRIME	kVA	1000
	kW	800



BAUDOUIN



Emsa



Datakom D700



Water Cooled



50 hz



3 phase



Easy maintenance



Modular type sound-proof canopy



Diesel



Remote control system



Warning system for decreasing fuel



Engine Specifications

- BAUDOUIN series heavy duty diesel engine
- 4 Cycle, Water Cooling system, TURBOCHARGED - INTERCOOLER Induction
- Electronic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

Model	6M26G550/5	
Power	Stand by kW	490
	Prime kW	448
Speed (rpm)	1500	
Cycle	4	
Displacement (lt)	15,9	
Number of cylinders	6, in line	
Bore & Stroke	150 x 150	
Compression ratio	15.7 : 1	

Governor type	Electronic	
Induction	TURBOCHARGED - INTERCOOLER	
Combustion System	Direct	
Cooling system	Water	
Fuel consumption (lt/h)	100%	106,8
	75%	79,8
	50%	54,5
Total lubrication system capacity (lt)	52	
Total coolant capacity (lt)	110,7	



Alternator Specifications

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid


Brand	Emsa	
Model	EGK315-400N	
Frequency (hz)	50	
Power (KVA)	550	
Design	4 pole, brushless	
Connection type	Star	
Voltage (V)	400	

phase	3	
A.V.R.	KR440	
Voltage regulation (+/-)	± 1%	
Insulation system	Class H	
Protection	IP23	
Rated power factor	0,8	
Weight (kg)	1202,5	



Canopy

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Weatherproof canopy rating is IP 23
- Canopy designed for easy maintenance



	Dimensions (W x L x H) mm	N/A
	Weight (Kg)	N/A
	Fuel tank capacity (lt)	2544

- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window
- Insulation details: Non-flammable acoustic foam
- Nano tech cleaning system
- Container optional



	Dimensions (W x L x H) mm	N/A
	Weight (Kg)	N/A
	Fuel tank capacity (lt)	2544

Silencer options

- Standard industrial type
- Critical type
- Hospital type

Gen-Set safety protection & alarms

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level

Optional Equipments

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Modular type sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets

Canopy options

- Standard canopy
- Super silent canopy
- Extra süper silent canopy (thicker insulation)

- Over current load
- High & low genset voltage
- Start/stop failure

- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system